

2. TOSS GRENADE GENTLY AND DESTROY ENEMY





Open crimp
 Coating of paint removed



- Closed crimp
 Coating of paint
- είοιε cartidges in a cool dry place


on a di sephintren enot?

• Cartridges which misfire are still live and should be treated as such

Do not rely on the striker's mark on the cartridge mim to determine if a cartridge has been fired. Misfires occur due to inconsistencies in cartridge manufacturing.

- FIREd cartridges will have an open crimp
- clear paint mark (brown, green, yellow)
- Unfired cartridges will have a closed crimp and a
- Only determine it a cartridge is fired by observing the crimped end of the cartridge

WISFIRES



NOTE: It is safe to "dry fire" this device with no cartridge loaded. All moving parts can tolerate being dry fired.


6. Do not attempt to troubleshoot this product with live rounds loaded. Unload and make safe before cleaning or storing this device.

5. Do not attempt to modify this product or you may make your grenade unsafe.

4. Do not attempt to remove the lower muffler can from the rest of the grenade body. The lower muffler can is intended to protect you from the dangerous gas expulsion from the cartridge so we have expulsion from the cartridge so we have the grenade to protect you! 3. This product is very loud! West appropriate hearing protection, especially when deploying it into closed areas indoor. Do not use high powered cartridges when using this product in confined spaces.

2. Be considerate. This product is heavy. Do not throw it directly at another player. Do not throw it very high or very forcefully.

I. I fine product discriatiges gas suddenly from it's exhaust ports at the bottom. Do hot block these ports with your head or point these ports towards your face EVER!. Wesr eye protection and gloves when using this product.



SAFETY

DEPLOYMENT

AIRSOFT INNOVATIONS

BALLISTICS

1. PULL PIN

BARG22 TIMER BANGER GRENADE



User manual 2x Bang 22 pull pins Assumption of risks: there is a serious risk of personal injury, death or property

KIT CONTAINS

Assumption of risks: there is a serious risk of personal injury, death or property damage arising out of the use or misuse of this product. By using this product, you agree to freely accept and fully assume all such risks.

CHOOSE YOUR CARTRIDGE

 Bang 22 is compatible with three nail driver cartridges which generate three different sound levels.

Cartridge	dBa@ 20ft	Application
Brown	118	CQB
Green	122	Loud CQB
Yellow	125	Outdoors
Red/Purple	Do not use	Will damage grenade

- Colours are painted on the tip of the cartridge.
- Bang 22 only accepts bottle-necked cartridges made by Ramset. Straight-body cartridges will not fit in Bang 22
- DO NOT use RED or PURPLE cartridges as these are too powerful and will permanently damage the grenade.
- DO NOT attempt to use firearms cartridges like .22 Short or .22LR

Bottleneck









Support:

RELOADING PROCEDURE


1. UNSCREW THE TIMER HEAD






2. SWING OUT CARTRIDGE GATE

Do not attempt to tighten screw Cartridge gate should be loose and jingle around. This is normal.



4. USE PULL PIN AS A LEVER TO PRY OUT CARTRIDGE



SET TIMER

5. INSERT PIN

Locate pull pin hole and insert pull pin.

6. SELECT TIMER DELAY


The temperature of your game environment affects your Bang 22's timer delay. Rotate the metal guard to select the appropriate temperature setting.

Cold day (5-15C°/40-60°F)


Medium day (B) (15-25C°/60-80°F)

Hot day (25C°+/80°F+)


This will provide you with a useable delay which can be changed at any time before use.



7. REPLACE CARTRIDGE



8. SWING GATE CLOSED



9. SCREW ON THE TIMER HEAD

Only screw on head AFTER timer is set.

10. BANG

Your Bang 22 is now ready to deploy. Treat it respectfully - it is loaded.

11. STORAGE

Remove unfired cartridges before storing Bang 22.

Store the grenade with the timer head on to prevent contaminants from entering it.

